

S & R Boat Rentals

HULL: 11704

MODEL: 2284VWB2

M/V: SR9

Hull

Length	22' (approx. 24'-4" LOA with motor bracket)
Bottom	1/4" aluminum plate 5086 12° deadrise
Side	3/16" 5086 Alloy plate. 36" Height with two corrugations per side.
Front Deck	3/16" tread plate. 72 " long with a 24" deck extension.
Frame Structure	PROVEN FRAME STRUCTURE Frame structure complies with USCG 46 CFR parts 177.3 structural design Subchapter "T" for small passenger Vessel (Deck Load Capacities) You must see and witness this frame structure. Please visit our plant.
Longitudinal Frames	4" x 3/8" flat bar keel inside of hull 2" x 2" x 3/8" angle keel protector Two - 3/16" flange plate girders
Transverse Frames	3" bulb tee spaced on 14" centers 2" square tubing spaced on 14" centers double bottom support
Transom	1/4" plate reinforced with 4" channel
Gunnel Cap	Outside 3" D shape rubber Inside aluminum tread plate
Double Bottom	1/8" tread plate, tested at 2 psi

Cabin

Dimensions	Cabin 8' long overall, 7' Inside, 1/8" plate, approximately 6'-4" tall, 4'-6" tall above gunnel. Reinforced with 1-1/4" x 1-1/4" x 1/8" tubing.
Cabin Forward	3 Dimensional Front. Center to be a door with safety glass, one door dog, and locking latch. Remaining two sections to have 1/4" safety glass installed. Two steps provided 18" wide from forward deck down into cabin.
Cabin Sides	Two horizontal slide windows, one port, one starboard approximately 4' long. Remaining section to have 1/4" safety glass installed.
Cabin Rear Bulkhead	Center to be a door with safety glass, one door dog, and locking latch. Remaining two sections to have 1/4" safety glass installed.
Cabin Exterior	Walkway around port and starboard approximately 10" wide. Handrail on top of cabin.

Cabin Inside

Captain Seat	One required Captain Seat Heavy duty with adjustable arm and back rest. Capable of sliding forward movement of 5" fwd and aft. Pedastol included
Storage/Seat 1	One port side seat with dry storage approx. 84" long with a 2" vinyl cushion on bottom and a 4" on the back
Storage/Seat 2	One starboard side seat with dry storage 70" long with a 2" vinyl cushion bottom and a 4" vinyl back cushion
Console	Starboard side console 28" wide
Instrument Box	One Instrument box on overhead of console Starboard side only

Fuel Tank

Note:	FUEL TANKS ARE USCG AND EPA COMPLIANT
Gas Fuel Tank	Two 40 gallon alum tank installed aft of cabin
Gas Fuel System	Two- Tempo inline two way valve. Two- Yahama Water Separator (canister style). Two- Teleflex Fuel Gauges Two wema fuel sending units Shields 3/8" Fuel Hose (USCG Ethonal approved).

Accessories

*** NOTE: ALL BOLTS, SREWS, CLAMPS, ETC., IS STAINLESS STEEL.**

ALL WIRING TO BE DOUBLE INSULATED MULT-STRAND COPPER WIRING AND ALL ELECTRICAL WIRE PENETRATIONS THRU BULHEADS HAVE RUBBER GROMMETS TO PREVENT STRAY CURRENT CORROSION, AND ELECTRICAL SHORT CIRCUITS, IN ACCORDANCE WITH ABYC AND USCG 46 CRF

		<u>Qty</u>
Engine Motor Bracket	Dual engine motor bracket extends out 30" fitted for 25" long shaft, with two machined aluminum inspection plates.	1
Engine Guardrail	Engine guardrail constructed of 2" sch 80 pipe with a 10" wide tread plate perimter.	1
Push Knees	4" solid Rubber Bumper Push Knee.	2
Mooring Cleats	7/8" alum rod welded to a 1" x 4" flat bar	4
Batteries	Deep Cycle Marine Battery 12V - 1000 cranking amps and battery box	2
Battery Switch	Perko 8501 Battery Switch or equal , 1,2,All.- position	2
Running Lights	LED side mount recess running lights LED 36" all around stowaway stern light Bluesea 6 fused switch panel 6 gang ground buss bar 6 gang fuse buss bar 70 amp fuse 12" from battery	1
Search Light	Perko 314 C07 250,000 CP search light, hand lever controll.	1
Cabin Lights	Sea Dog 12V DC cabin light, polished stainless with switch.	1

12V Receptacle	Sea Dog 12V receptacle	1
Bilge Pump	Rule 2000 gph, 12V automatic bilge pump, stainless thru hull fitting.	1
Windshield Wiper	Imtra heavy duty windshield wiper, 12V DC.	1
Horn	Marinco single trumpet ,stainless.	1
VHF Radio	Uniden Oceanus VHF Radio, with 8' antenna and mount.	1
Anodes	5 Lb magnesium anodes.	2
Fire Extinguisher	10B:C fire extinguisher 5 lb, USCG approved with bracket.	1
Steering	Seastar hydraulic steering for dual outboards, with dual cylinders, stainless tie bar, stainless steel steering wheel with swival knob.	1
Trim Tabs	LectroTab with rocker switch.	1
Motor	Yamaha F115HP four stroke outboards, 25" Shaft, mechanical control box, cables, stainless propeller and digital tachometers.	2
Safety Equipment	Four - 7-1/2" x 12' nylon mooring line Two - Stickers "Gasoline" Two - Stickers "No Smoking"	1
Life Ring	24" orange life ring with hanger	1
Life Jacket	Adult Yolk life jackets with reflector	6
Anchor	#5 anchor with 5' of 1/4" galv chain, and 50' of 1/2" nylon rope.	1
Signal Kit	Flare gun kit	1
First Aid Kit	First Aid Kit (6 person)	1

Trailer

Trailer

Magic Tilt Model TCA 2482
All welded Aluminum - Tandem Axle
15" Tires 8200 Lbs. Load Net Capacity
Side Boards, Buddy Bearings, Jack.
Vertical Winch post with a ladder
Disc Brakes on all axles.
Spare Tire & Bracket.