

Scully's Inc

1015 Stephenville Road
Morgan City, LA 70380
Phone: 985-385-1323 Fax: 985-384-5146
Website: <http://www.scullyboats.com>
Email: info@scullyboats.com

Quote: 1294
2284VWB2

Tuesday, September 15, 2015

Scully's Aluminum Boats
Used Boat Specification

Attn: Elwood Scully



Picture may vary from items quoted below.

Customer Contact Info:

Phone: (985) 385-1323

Fax:

Cell: (985) 518-9520

Email: elwood@scullyfab.com

Subject: 2284VWB2

Dear Sir,

Scully's Aluminum Boats, Inc. proposes to furnish labor and materials to construct one Aluminum Work Boat as per the following:

Hull

Length	22' (approx. 24'-6" LOA with motor bracket)
Beam	8' - 6"
Bottom	1/4" aluminum plate, 5086 alloy. 7' wide shallow vee
Side	3/16" plate, 5086 alloy. 36" height
Deck	1/8" tread plate, 6' Long
Frame Structure	TWENTY-FIVE YEAR PROVEN FRAME STRUCTURE Complies with USCG 33 CFR Subchapter "I" Cargo Vessel (Deck Load Capacities) You must see and witness this frame structure. Please visit our plant.
Longitudinal Frames	4" x 3/8" Flat Bar Keel. Two - Flange plate girders approx. 12" deep x 3/16" from bow to stern.
Transverse Frames	3" I-Beam spaced 14" centers 2" x 2" x 3/16" square tubing spaced on 14" centers
Transom	3/16" aluminum plate, 5086 alloy
Gunnel Cap	Outside 3" D shape rubber one required around perimeter Inside approx. 10" wide tread plate.
Double Bottom	1/8" tread plate, from fwd deck to transom.

Cabin

Dimensions	Length approximately 8' long, 7' Inside, 1/8" plate. Height approximately 6'-4" tall on centerline. Reinforced with 1-1/4" x 1-1/4" x 1/8" tubing.
------------	--

Cabin Forward	3 Dimensional Front, center to be a door with safety glass, one door dog, and locking latch. Two steps provided 18" wide Remaining sections to have safety glass installed.
Cabin Sides	Two horizontal slide windows, one port, one stb. Remaining section to have safety glass installed.
Cabin Rear Bulkhead	Center to be a door with safety glass, and one Stainless steel door dogs,locking latch. Remaining two sections to have safety glass installed.
Cabin Exterior	Walkway around port and starboard approx. 10" wide.

Cabin Inside

*NOTE:	NOTE: Cabin intended to carry Six (6) persons.
Captian Seat	Heavy duty, with adjustable arm rest and high backrest.
Storage/Seat 1	One stb bench seat approx. 50" long with a 2" vinyl cushion bottom and a 4" vinyl cushion back.
Storage/Seat 2	One port bench seat approx. 84" long with a 2" vinyl cushion bottom and 4" vinyl cushion back.
Console	Stb side, 24" wide
Instrument Box	One Instrument box on the forward overhead in cabin.

Fuel Tank

Note:	ALL FUEL HOSES ARE USCG APPORVED, DOUBLE HOSE S.S.CLAMPS ON EACH END OF HOSES.FUEL TANKS ARE EQUIPED WITH TAG LABELS AND CONTAINMENT BOXES AS PER USCG 33 CFR
Gas Fuel Tank	Two - 40 gallon alum tank bolted rear of cabin. 1-1/2" fill , suction and vent, with spill containment box.
Gas Fuel System	Two - Tempo inline two way valve. Two - Water Separator (canister style). Two - Fuel Gauges. Shields 3/8" Fuel Hose (USCG approved).

Accessories

*** NOTE: ALL BOLTS, SREWS, CLAMPS, ETC., IS STAINLESS STEEL.**

ALL BULKHEADS HAVING ELECTRICAL WIRE PENETRATIONS HAVE RUBBER GROMMETS TO PREVENT ELECTROLYSIS

		<u>Qty</u>
Engine Motor Bracket	Dual Engine Motor Bracket extends out 30" fitted for a 25" shank outboards.	1
Engine Guardrail	Engine guardrail constructed of 2" sch 80 pipe, with trad plate perimeter.	1
Push Knees	3" Solid rubber bumper push knees.	2
Mooring Cleats	Lifting eyes, 4" x 1" aluminum flat bar with a 1" aluminum round rod bit.	4
Batteries	Deep Cycle Marine Battery 12V -1000 amps,and box.Two batteries will be set up from one main engine for charging system. One for house battery all 12 volt system.will use .The other battery wiil be carged from the main engine systemNo extra charging system	2
Battery Switch	Perko 8501 Battery Switch 1,2,all.	1
Running Lights	Perko side mount eunning lights. Attwood 24" all around stowaway stern light. Blue sea six switch fused panel	1
Search Light	Perko 314 C07 search Light 250,000 CP, full rotation lever.	1
Cabin Lights	Sea Dog cabin light, polished stainless.	1

12V Receptacle	Sea Dog 12V receptacle.	1
Bilge Pump	Rule 2000 gph 12V automatic bilge pump.	1
Windshield Wiper	Imtra heavy duty windshield wiper, 12V.	1
Horn	Marinco single trumpet horn, stainless.	1
GPS	Garman GPS, with external antenna.	1
Anodes	5 Lb Magnesium Anodes.	2
Steering	Seastar Hydraulic Steering for dual engine, with dual cylinders and stainless tie bar.	1
Trim Tabs	Lenco Marine 12V electric trim tabs.	1
Motor	115 HP Yamaha four stroke outboard, 25" shaft, controls, cables, stainless props, Yamaha digital tachs	2
Air Conditioner	Coleman SeaMach 13,500 BTU A/C with Heat 110v AC.	1
Roof Insulation	1" foam insulated roof with ornite cover.	1

Trailer

Trailer	Magic Tilt Model TCA2482 Aluminum / Dual Axle. 15" Tires, 8200 Lb Net Capacity Buddy Bearings, Jack
Hydraulic Brakes	Disc Brakes on all axles.
Spare Tire	Spare Tire & Bracket.