

# Scully's Inc

1015 Stephenville Road  
Morgan City, LA 70380

Phone: 985-385-1323 Fax: 985-384-5146

Website: <http://www.scullyboats.com>

Email: [info@scullyboats.com](mailto:info@scullyboats.com)

Quote: 1295

2896BS1

Tuesday, June 21, 2011

## Scully's Aluminum Boats

Used Boat Specification

Attn: Elwood Scully



Picture may vary from items quoted below.

### Customer Contact Info:

Phone: (985) 385-1323

Fax:

Cell: (985) 518-9520

Email:

Subject: 2896BS1

Dear Sir, Ma

Scully's Aluminum Boats, Inc. proposes to furnish labor and materials to construct one Aluminum Work Boat as per the following:

### Hull

Length	28' (30'-5" with motor bracket)
Beam	8' - 2"
Bottom	3/16" aluminum plate, 5086 alloy, 8' wide flat bottom.
Side	3/16" aluminum plate. 30" height
Deck	3/16" aluminum tread plate.
Longitudinal Frames	3" aluminum bulb tee spaced on 12" centers.
Transverse Frames	5" x 1/4" aluminum flange plate spaced on 28" centers
Transom	3/16" plate reinforced with 4" channel.
Gunnel Cap	3"D rubber perimeter top Second run of aluminum rubrail
Bulkhead	Two bulkheads. three water tight compartments.

### Floor Plan

Console	40" wide x 36" tall, located on aft centerline.
Windshield	Aluminum frame with 1/4" safety glass.
Instrument Box	1/8" aluminum installed overhead of T-Top
T-Top	1/8" aluminum hard-top approx. 72" long x 48" wide.
Captains Seats	Bench seat dry storage with bottom cushion.

### Fuel Tank

Note: ALL FUEL HOSES ARE USCG APPROVED, FUEL TANKS ARE EQUIPED WITH TAG LABELS AS PER USCG 46 CFR

Gas Fuel Tank One - 100 gallon tank mounted thru console.

Gas Fuel System Two - Tempo inline valve.  
Two - Water separator  
One - Fuel gauge  
Shield 3/8" fuel hose (USCG approved)

## Accessories

**\* NOTE: ALL BOLTS, SREWS, CLAMPS, ETC., IS STAINLESS STEEL.**

ALL BULKHEADS HAVING ELECTRICAL WIRE PENETRATIONS HAVE RUBBER GROMMETS TO PREVENT ELECTROLYSIS

		<u>Qty</u>
Handrails	38" tall, two-runs, 4" kick plate, from transom to bow. Chain across bow and transom.	1
Hatch	Quick acting manhole hatch with hinge. One for each compartment.	3
Engine Motor Bracket	Dual Engine Motor Bracket extends 30" fitted for a 25" long shank outboards.	1
Engine Guardrail	2" sch 80 pipe, 10" wide tread plate perimeter.	1
Push Knees	4" solid rubber bumper.	2
Mooring Cleats	6" x 1" flat bar with 3/4" rod for bit.	4
Tow Bit	4" sch 80 aluminum pipe, 36" tall with 1-1/2" rod thru.	1
Batteries	Deep cycle marine battery, 12V, 900 cranking amps.	1
Battery Switch	Perko 8501 battery switch, 3-position. 1,2,All	1
Running Lights	Side mount running lights 24" all around stowaway stern light 6 gang switch panel. Fuse buss bar.	1
Search Light	Jabsco remote spotlight 100,000 candle power.	2
12V Receptacle	Sea Dog 12V Receptacle.	1
Bilge Pump	Rule 2000 gph, 12V, automatic.	3
Windshield Wiper	United Tecnology windshield wiper, heavy duty, 12V.	1
Horn	Sea dog single trumpet horn, stainless.	1
GPS	Garman GPS 541S with transducer.	1
VHF Radio	Uniden Oceanus VHF radio, with 8' antenna.	1
Anodes	5 Lb magnesium anodes.	2
Fire Extinguisher	10B:C USCG approved with bracket.	1
Paint	Blast and Paint Waterline down 14 mills of epoxy then 14 mills Trilux 33 antifouling paint.	1
Steering	Seastar hydraulic steering for dual engine with dual cylinders and stainless tie bar stainless steering wheel.	1
Trim Tabs	Lenco Marine, 12V, electric trim tabs.	1
Motor	115 HP Yamaha four stroke outboards, 25" shaft, controls, cables, stainless props, Yamaha digital tachometers.	2
Trailer	Magic Tilt Model: TCA2882 Aluminum - Tandem axle 16" Tires 10000 Lbs. net load capacity Guide post , buddy bearings, jack with foot. Hydraulic Surge Brakes Spare Tie	